

# INFORMAÇÃO DE PRODUTO

## CARACTERÍSTICAS TÉCNICAS



### BRICK 600

**Description** Thick PU plotter cut material, with polyester backing, available with matt finish.

Despite the outstanding thickness, the material grants easy cutting, weeding and application and a high washing resistance. Suitable for cotton, polyester, performance wear, poly/cotton blends and spandex, not treated or dye sublimated.


**Usage** Preheat the press for 2 minutes at 155°C.


- Mirror cut the material
- Weed the exceeding material
- Place the material on the garment with its polyester backing
- Heat apply at the conditions shown on the right
- Remove the carrier cold


**Washing** Wait at least 24 hours from application before washing. Washing resistance up to 60°C, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Suitable for tumble dry, cotton program.

The product is REACH compliant  
The product is Öko-Tex® Standard 100 Class II certified  
The product is VEGANOK certified



 **Average thickness**  
600 microns

 **Suggested cutting settings**  
Blade: 60°  
Pressure: 80 gf  
Speed: 10 cm/sec

 **Transfer settings**  
25 seconds at 155°C  
(310°F)  
medium pressure  
(3-4 bar)

Washing temperature



Dry cleaning



Tumble dryer



**N.B.** All information here contained are based on our experience. We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C.