

INFORMAÇÃO DE PRODUTO

CARACTERÍSTICAS TÉCNICAS



BRICK

Description Very thick PU plotter cut material, with polyester backing, available with matt or glossy finish.
Despite the outstanding thickness, the material grants easy cutting, weeding and application and a high washing resistance.
Suitable for cotton, polyester, performance wear, poly/cotton blends and spandex, not treated or dye sublimated

Usage Preheat the lower press plate for 15 seconds at 155°C.
Due to thickness it is possible to cut letters of 2 cm height minimum.

- Mirror cut the material
- Weed the exceeding material
- Place the material on the garment with its polyester backing
- Heat apply at the conditions shown on the right
- Remove the carrier cold

For glossy colors GOLD and SILVER:


- Heat apply at the conditions shown on the right
- Remove the carrier cold
- Cover with silicon paper or teflon and press again for 5 seconds


Washing Wait at least **24 hours** from application before washing.
Washing resistance up to **60°C**, best inside-out.
Do not use bleach or other aggressive chemical agents.
Not suitable for dry cleaning.
Suitable for tumble dry, cotton program.


The product is REACH compliant
The product is Öko-Tex® Standard 100 Class II certified
The product is VEGANOK certified



N.B. All information here contained are based on our experience.
We recommend to perform a test before starting standard production.
For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C

 **Average thickness**
1000 microns

 **Suggested cutting settings**
Blade: 60°
Pressure: 150 gf
Speed: 10 cm/sec

 **Transfer settings**
25 seconds at 155°C
(310°F)
medium pressure
(3-4 bar)

Washing temperature



Dry cleaning



Tumble dryer

