

INFORMAÇÃO DE PRODUTO

CARACTERÍSTICAS TÉCNICAS




FOIL


Description Thin PU plotter cut heat seal material with adhesive polyester backing featuring metallic aspect.


The material grants a good workability during the weeding and application phases. It is not possible to overlay on the material.

Suitable for cotton, polyester, performance wear, poly/cotton blends and spandex, not treated or dye sublimated

- Usage**
- Mirror cut the material
 - Weed the exceeding material
 - Place the material on the garment with its polyester backing
 - Heat apply at the conditions shown on the right
 - Remove the carrier warm

 **Average thickness**
100 microns

 **Suggested cutting settings**
Blade: 45°
Pressure: 50 gf
Speed: 20 cm/sec

 **Transfer settings**
15 seconds at 135°C (275°F)
medium pressure (3-4 bar)

Washing Wait at least **24 hours** from application before washing. Washing resistance up to **40°C**, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Not suitable for tumble dryer.

The product is REACH compliant
The product is certified Öko-Tex® Standard 100 Class I
The product is VEGANOK certified



Washing temperature



Dry cleaning



Tumble dryer



N.B. All information here contained are based on our experience. We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C