

INFORMAÇÃO DE PRODUTO

CARACTERÍSTICAS TÉCNICAS





COLORPRINT PU


Description Thin PU heat seal material with polyester backing, created for inkjet digital printing & cutting systems with solvent, eco-solvent or HP Latex based inks. Available with matt or glossy finish.

Suitable for cotton, polyester, performance wear, poly/cotton blends and spandex, not treated or sublimated.

- Usage**
- Print and cut the material
- When printing on HP Latex plotter, set the drying temperature at 70°C*
- Weed the exceeding material
 - Remove the print from the polyester backing using Siser's TTD (adhesive, transparent and resistant to high temperatures)
 - Heat apply at the conditions shown on the right
 - Remove the application tape warm (in case of other application tapes, follow specific instructions)

 **Average thickness**
80 microns

 **Suggested cutting settings**
Blade: 45°
Pressure: 65 gf
Speed: 25 cm/sec

 **Transfer settings**
15 seconds at 155°C (310°F)
medium pressure (3-4 bar)

Washing Wait at least **24 hours** from application before washing. Washing resistance up to **60°C**, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Suitable for tumble dry, cotton program.

The product is REACH compliant
The product is certified Öko-Tex® Standard 100 Class I
The product is certified for print with HP Latex inks
The product is VEGANOK certified

Washing temperature



Dry cleaning



Tumble dryer



N.B. All information here contained are based on our experience. We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C