


INFORMAÇÃO DE PRODUTO

CARACTERÍSTICAS TÉCNICAS




COLORPRINT PU EXTRA SP

Description Thin PU heat seal material with polyester backing, created for inkjet digital printing & cutting systems with solvent, eco-solvent or HP Latex based inks. Available with matt or glossy finish.

 **Average thickness**
70 microns

Suitable for nylon or polyamide silicon treated textiles (eg. K-way, windbreakers, sport jackets, umbrellas, etc.) and also for leather.


 **Suggested cutting settings**
Blade: 45°
Pressure: 75 gf
Speed: 25 cm/sec

Usage

- Print and cut the material

When printing on HP Latex plotter, set the drying temperature at 75°C

- Weed the exceeding material
- Remove the print from the polyester backing using Siser's TTD (adhesive, transparent and resistant to high temperatures)
- Heat apply at the conditions shown on the right
- Remove the application tape warm (in case of other application tapes, follow specific instructions)

 **Transfer settings**
15 seconds at 155°C (310°F)
medium pressure (3-4 bar)

Washing Wait at least **48 hours** from application before washing. Washing resistance up to **40°C**, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Suitable for tumble dry, syntetic program.

Washing temperature



Dry cleaning



Tumble dryer



N.B. All information here contained are based on our experience. We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C