

INFORMAÇÃO DE PRODUTO

CARACTERÍSTICAS TÉCNICAS



JETFLOCK SOLVENT


Description Polyester flock material with paper backing, created for inkjet digital printing & cutting systems with solvent and eco solvent based inks. It features high covering power, brilliant color reproduction and easy workability.


Suitable for cotton, polyester, performance wear, poly/cotton blends and spandex (not suited for treated and sublimated textiles).


- Usage**
- Print and cut the material
 - Let the print dry at least 2 hours before rolling, overlaying or heat transferring the material
 - Weed the exceeding material
 - Remove the print by hand (in case of lettering use a suitable application tape)
 - Place the material on the garment
 - Cover with silicon treated paper or Teflon® (or application tape)
 - Heat apply at the conditions shown on the right
 - Remove the carrier cold

Washing Wait at least **24 hours** from application before washing. Washing resistance up to **60°C**, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Suitable for tumble dry, syntetic fibers cycle.

The product is REACH compliant

 **Average thickness**
450 microns

 **Suggested cutting settings**
Blade: 45°
Pressure: 120 gf
Speed: 20 cm/sec

 **Transfer settings**
15 seconds at 180°C
(356°F)
media
(3-4 bar)

Washing temperature



Dry cleaning



Tumble dryer



N.B. All information here contained are based on our experience. We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C