


INFORMAÇÃO DE PRODUTO

CARACTERÍSTICAS TÉCNICAS




P.S. ELECTRIC


Description PU plotter cut heat seal material with adhesive polyester backing and bright colors. The material grants a good workability during the weeding and application phases and is highly wash-resistant. Recommended for overlaying applications.

 **Average thickness**
90 microns

Suitable for cotton, polyester, blends of these materials (not suited for treated or dye sublimated textiles)

 **Suggested cutting settings**
Blade: 45°
Pressure: 60 gf
Speed: 30 cm/sec

- Usage**
- Mirror cut the material
 - Weed the exceeding material
 - Place the material on the garment with its polyester backing
 - Heat apply at the conditions shown on the right
 - Remove the carrier warm or cold

 **Transfer settings**
15 seconds at 150°C
(300°F)
medium pressure
(3-4 bar)

Washing Wait at least **24 hours** from application before washing. Washing resistance up to **60°C**, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Suitable for tumble dry, cotton cycle.

Washing temperature



Dry cleaning



Tumble dryer



The product is REACH compliant

The product is certified Öko-Tex® Standard 100 Class I

The product is VEGANOK certified



N.B. All information here contained are based on our experience. We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C