

INFORMAÇÃO DE PRODUTO

CARACTERÍSTICAS TÉCNICAS



P.S. FILM

Description PU plotter cut heat seal material with adhesive polyester backing featuring bright colors.
The material grants high washing resistance and an easy cutting, weeding and application. Suitable for multilayer applications. Fluo colours can leave traces on the support.

Suitable for cotton, polyester and poly/cotton blends (not suited for treated and dye sublimated textiles)


- Usage**
- Mirror cut the material
 - Weed the exceeding material
 - Place the material on the garment with its polyesterbacking
 - Heat apply at the conditions shown on the right
 - Remove the carrier warm or cold


Washing Wait at least 24 hours from application before washing. Washing resistance up to 80°C, best inside-out. Do not use bleach or other aggressive chemical agents. Suitable for dry cleaning. Suitable for tumble dry, cotton cycle.


The product is REACH compliant
The product is certified Öko-Tex® Standard 100 Class I
The product is VEGANOK certified



N.B. All information here contained are based on our experience. We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C

 **Average thickness**
90 microns

 **Suggested cutting settings**
Blade: 45°
Pressure: 90 gf
Speed: 30 cm/sec

 **Transfer settings**
15 seconds at 150°C (300°F)
medium pressure (3-4 bar)

Washing temperature



Dry cleaning



Tumble dryer

