INFORMAÇÃO DE PRODUTO CARACTERÍSTICAS TÉCNICAS




P.S. FILM EXTRA

Description Thin PU plotter cut heat seal material with adhesive polyester backing and large colours palette. The material grants a good workability during the weeding and application phases and is highly wash-

> Designed for application on nylon or polyammide silicon treated textiles (eg. K-way, windbreakers, sport jackets, umbrellas, etc.) and also leather.

Usage • Mirror cut the material

- Weed the exceeding material
- Place the material on the garment with its polyesterbacking
- Heat apply at the conditions shown on the right
- Remove the carrierwarm or cold



Suggested cutting settings

Blade: 45° Pressure: 50 gf Speed: 30 cm/sec

Transfer settings

15 seconds at 160°C (320°F) medium pressure (3-4 bar)

Washing Wait at least 24 hours from application before washing. Washing resistance up to 80°C, best inside-out. Do not use bleach or other aggressive chemical agents. Suitable for dry cleaning. Suitable for tumble dry, cotton cycle.

> The product is REACH compliant The product is certified Öko-Tex® Standard 100 Class I The product is VEGANOK certified







Washing temperature



Dry cleaning



Tumble dryer



N.B. All information here contained are based on our experience.

> We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C

