INFORMAÇÃO DE PRODUTO CARACTERÍSTICAS TÉCNICAS




P.S. METALLIC

Description Plotter cut heat seal material with adhesive polyester backing and a gold or silver metallic finish.

> Due to the unique nature of its metallic surface, it can be used for medium to large cuttings and single layer applications only. Avoid bending the application once transferred.

Suitable for cotton, polyester or poly/cotton blends, not treated or dye sublimated

- **Usage** Mirror cut the material
 - Weed the exceeding material
 - Place the material on the garment with its polyester backing
 - Heat apply at the conditions shown on the right
 - · Remove the carrier warm or cold



Suggested cutting settings

Blade: 60° Pressure: 130 gf Speed: 15 cm/sec

Transfer settings

15 seconds at 160°C (320°F) medium pressure (3-4 bar)

Washing

Wait at least 24 hours from application before washing. Hand washing recommended, best if inside-out.

Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Not suitable for tumble dryer.

The product is REACH compliant





Washing temperature



Dry cleaning



Tumble dryer



N.B. All information here contained are based on our experience.

> We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C