# INFORMAÇÃO DE PRODUTO CARACTERÍSTICAS TÉCNICAS



## P.S. PERFOR

**Description** PU plotter cut heat seal material with adhesive polyester backing featuring bright colors.

> The material grants high washing resistance and an easy cutting, weeding and application. Recommended for multilayer applications. The circular perforation allows transpiration, giving at the same time a unique decorating effect.

> Suitable for cotton, polyester, blends of these materials, not treated or dye sublimated.

# settings

Blade: 45° Pressure: 80 gf Speed: 30 cm/sec

**Suggested cutting** 

Average thickness

90 microns

- **Usage** Mirror cut the material
  - Weed the exceeding material
  - Place the material on the garment with its polyester backing
  - Heat apply at the conditions shown on the right
  - Remove the carrier warm or cold

### **Transfer settings**

15 seconds at 150°C (300°F) medium pressure (3-4 bar)

## **Washing**

Wait at least 24 hours from application before washing. Washing resistance up to 60°C, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Suitable for tumble dry, cotton cycle.

The product is REACH compliant The product is certified Öko-Tex® Standard 100 Class I The product is VEGANOK certified







Washing temperature



Dry cleaning



Tumble dryer



N.B. All information here contained are based on our experience. We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C