

INFORMAÇÃO DE PRODUTO

CARACTERÍSTICAS TÉCNICAS



P.S. STRETCH

Description PU plotter cut heat seal material with adhesive polyester backing. The material is thin, elastic, soft to the hand and blends well into the textiles, granting also an easy weeding and application. Specifically designed for textiles featuring elastic qualities.

Suitable for cotton, polyester, performance wear, poly/cotton blends and spandex, not treated or dye sublimated.


- Usage**
- Mirror cut the material
 - Weed the exceeding material
 - Place the material on the garment with its polyester backing
 - Heat apply at the conditions shown on the right
 - Remove the carrier warm or cold


Washing Wait at least **24 hours** from application before washing. Washing resistance up to **60°C**, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Suitable for tumble dry, cotton cycle.


The product is REACH compliant
The product is certified Öko-Tex® Standard 100 Class I
The product is VEGANOK certified



N.B. All information here contained are based on our experience. We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C

 **Average thickness**
90 microns

 **Suggested cutting settings**
Blade: 45°
Pressure: 50 gf
Speed: 20 cm/sec

 **Transfer settings**
20 seconds at 160°C
medium pressure
(3-4 bar)

Washing temperature



Dry cleaning



Tumble dryer

