INFORMAÇÃO DE PRODUTO CARACTERÍSTICAS TÉCNICAS



SOFT PRINT COLOR

Description Thin PU heat seal material with polyester backing, created for inkjet digital printing & cutting systems with solvent or eco solvent inks. Available with matt or glossy finish. Despite being very thin, the material grants a high covering power on dark fabrics.

> Suitable for cotton, polyester, performance wear, poly/co tton blends and spandex, not treated or dye sublimated

- **Usage** Print and cut the material
 - Weed the exceeding material
 - Remove the print from the polyester backing using Siser's TTD (adhesive, transparent and resistant to high temperatures)
 - Heat apply at the conditions shown on the right
 - Remove the application tape warm (in case of other application tapes, follow specific instructions)



Average thickness

Suggested cutting settings

> Blade: 45° Pressure: 60 gf Speed: 30 cm/sec



Transfer settings

15 seconds at 155°C (311°F) medium pressure (3-4 bar)

Washing

Wait at least 24 hours from application before washing. Washing resistance up to 40°C, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Not suitable for tumble dryer.

The product is REACH compliant The product is certified Öko-Tex® Standard 100 Class I The product is VEGANOK certified







Washing temperature



Dry cleaning



Tumble dryer



N.B. All information here contained are based on our experience. We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C

