

INFORMAÇÃO DE PRODUTO

CARACTERÍSTICAS TÉCNICAS



SPARKLE

Description PU based plotter cut heat transfer vinyl with smooth glitter surface and adhesive polyester backing. Excellent for multilayer application.

Suitable for cotton, polyester, poly/cotton blends, elastic fabrics and spandex (not suited for treated and sublimated textiles).

- Usage**
- Mirror cut the material
 - Weed the exceeding material
 - Place the material on the garment with its polyester backing
 - Heat apply at the conditions shown on the right
 - Remove the carrier warm

Washing Wait at least 24 hours from application before washing. Washing resistance up to 80°C, best inside-out. Do not use bleach or other aggressive chemical agents. Suitable for dry cleaning. Suitable for tumble dry, cotton cycle.

The product is REACH compliant
The product is certified Öko-Tex® Standard 100 Class I
The product is VEGANOK certified



Average thickness
120 microns



Suggested cutting settings
Blade: 45°
Pressure: 80 gf
Speed: 25 cm/sec



Transfer settings
15 seconds at 155°C (311°F)
medium pressure (3-4 bar)

Washing temperature



Dry cleaning



Tumble dryer



N.B. All information here contained are based on our experience. We always recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight at temperatures between 65°F and 80°F