


INFORMAÇÃO DE PRODUTO

CARACTERÍSTICAS TÉCNICAS




STRIPFLOCK PRO


Description Plotter cut flock material with brilliant colours, suitable for cotton, polyester, poly/cotton blends (not suitable for dye sublimated fabrics). Adhesive polyester carrier.

 **Average thickness**
500 microns

Stripflock Pro cannot be layered on itself.

- Usage**
- Mirror cut the material
 - Weed excess material
 - Place it on the garment with its polyester carrier
 - Heat apply at the conditions shown on the right
 - Remove the carrier warm

 **Suggested cutting settings**
Blade: 60°
Pressure: 80 gf
Speed: 15 cm/sec

 **Transfer settings**
15 seconds at 155°C (311°F)
medium pressure (3-4 bar)

Washing Wait at least **24 hours** from application before washing. Washing resistance up to **60°C**, best inside-out. Do not use bleach or other aggressive chemical agents. Do not dry clean. Suitable for tumble dry, cotton cycle.

Washing temperature



Dry cleaning



Tumble dryer



The product is REACH compliant
The product is certified Öko-Tex® Standard 100 Class I
The product is VEGANOK certified



N.B. All information here contained are based on our experience. We recommend to perform a test before starting standard production. For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C