

INFORMAÇÃO DE PRODUTO

CARACTERÍSTICAS TÉCNICAS



SUBLITHIN™ MATT LT

Description PU heat seal material with polyester backing, created for inkjet digital printing & cutting systems with solvent, eco-solvent or HP Latex based inks. Specifically conceived for transfers on polyester textiles colored with dye sublimation, prevents color migration, stopping sublimation effects.


Suitable for polyamide or polyester fabrics not treated.


- Usage**
- Print and cut the material
 - Weed the exceeding material
 - Remove the print from the polyester backing using Siser's TTD (adhesive, transparent and resistant to high temperatures)
 - Heat apply at the conditions shown on the right
 - Remove the application tape warm (in case of other application tapes, follow specific instructions) Do not stack or fold the clothings warm in order to avoid staining of the external surface


Washing Wait at least **24 hours** from application before washing. Washing resistance up to **40°C**, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Not suitable for tumble dryer.

The product is REACH compliant
The product is certified Öko-Tex® Standard 100 Class I
The product is VEGANOK certified



 **Average thickness**
110 microns

 **Suggested cut settings**
Blade: 45°
Pressure: 100 gf
Speed: 20 cm/sec

 **Transfer settings**
15 seconds at 135°C
(275°F)
medium pressure
(3-4 bar)

Washing temperature



Dry cleaning



Tumble dryer



N.B. All information here contained are based on our experience.
We recommend to perform a test before starting standard production.
For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C