



## T.T.D. Application Tape

**Description** Adhesive Polyester Film for the correct application of digital printing materials. It is available in three different grades of adhesion :  
ADVANCED, EASY and EVOLUTION.

The adhesive side of the material is protected with silicon paper.



**Average thickness**  
75 microns

### Range of application

PRODUCT	TTD ADVANCED (low tack)	TTD EASY (medium tack)	TTD EVOLUTION (high tack)
COLORPRINT	■	■	■
COLORPRINT EXTRA	■	■	■
COLORPRINT NEW M		■	■
COLORPRINT PU / MATT		■	■
COLORPRINT PU EXTRA / MATT		■	■
DIGITAL PERFOR		■	■
HI-5 PRINT MATT		■	■
SOFT PRINT COLOR VIVID / MATT		■	
SUBLITHIN MATT LT		■	■

**Procedure** Remove the protective paper from T.T.D.  
Apply the T.T.D. onto the printed logo, manually using a laminator, avoiding air bubbles  
Remove the backing of the digital, printed media  
Heat apply following the instructions of the digital media  
Remove T.T.D. Advanced according the given instructions for the product in use..

The product is REACH approved.

**N.B.** All information here contained are based on our experience.  
We recommend to perform a test before starting standard production.  
For best results we suggest to store the product away from sunlight and dust, in vertical position and at temperatures between 18°C and 26°C