

INFORMAÇÃO DE PRODUTO

CARACTERÍSTICAS TÉCNICAS





VIDEOFLEX PU


Description PU plotter cut heat seal material with polyester backing. The material grants high washing resistance and an easy cutting, weeding and application. Recommended for multilayer applications.

Suitable for cotton, polyester, blends of these materials, not treated or dye sublimated fabrics.

- Usage**
- Mirror cut the material
 - Weed the exceeding material
 - Place the material on the garment with its polyester backing
 - Heat apply at the conditions shown on the right
 - Remove the carrier cold

 **Average thickness**
85 microns

 **Suggested cutting settings**
Blade: 45°
Pressure: 50 gf
Speed: 30 cm/sec

 **Transfer settings**
15 seconds at 150°C (302°F)
low pressure(2-3 bar)

Washing Wait at least **24 hours** from application before washing. Washing resistance up to **60°C**, best inside-out. Do not use bleach or other aggressive chemical agents. Not suitable for dry cleaning. Suitable for tumble dry, synthetic cycle.

The product is REACH compliant
The product is certified Öko-Tex® Standard 100 Class II



Washing temperature



Dry cleaning



Tumble dryer



N.B. We always recommend to perform a test before starting standard production.
All information here contained are based on our experience.
For best results we suggest to store the product away from sunlight at temperatures between 65°F and 80 °F, vertical position.



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9105027958



The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance). This document can be subject to variations. Updated versions are available on our website www.siser.com
For further information, please contact our Sales Office.